


CANGURO PROFESSIONAL SUPER

**TRINCIAERBA/ TRINCIASARMENTI
CON RACCOLTA PER TRATTORI DA 55 A 70 CV
CONTRACTOR FLAIL MOWER
FOR TRACTORS FROM 55 TO 70 HP**

VIDEO 




Caratteristiche

- Con raccolta e scarico in altezza a 200cm*.
- Macchina robusta per lavori intensivi.
- Per utilizzo con trattori da 50 a 80CV.
- Per superfici comunali, agricole (Vigneti e Frutteti) maneggi, ippodromi e orticoltura.
- Taglio erba fino a 200cm di altezza.
- Triturazione rami fino a 6cm di diametro.
- Cuscinetti UCC su albero coltelli ad alta resistenza da urti ed attriti.
- Moltiplicatore con ruota libera.
- Apertura raccogliitore idraulica con 2 prese.
- Rullo posteriore autopulente.

Features

- With collection and high lift discharge at 200cm* height.
- Sturdy machine for intensive work.
- For 50 to 80 HP tractors use.
- For municipal, agricultural fields (vineyards and orchards), stables, racetracks, and horticulture.
- Grass cutting up to 200 cm in height.
- Branch shredding up to 6 cm in diameter.
- UCC bearings on the flail shaft, high resistant to impacts and friction.
- Gearbox with overrun clutch.
- Hydraulic collector opening with 2 quick couplings.
- Self-cleaning rear roller.



MODELLO MODEL		 (MIN - MAX)		
	(MM)	(HP)	(KW)	Nr.
CANGURO PROFESSIONAL SUPER 1600	1525	50 - 65	37 - 48	20
CANGURO PROFESSIONAL SUPER 1800	1720	60 - 80	45 - 60	24



Scarico idraulico oltre 2 mt
High lift discharge up to 2 mt



COMPONENTI TECNICHE DI SERIE TECHNICAL COMPONENTS STANDARD



Facile tensione cinghie.
Easy belts tightening
adjustment.




Rullo posteriore con
raschiatore.
Rear roller with scraping bar.

ACCESSORI ACCESSORIES



Regolazione dell'altezza
di taglio su ruote frontali
doppie.
Height of cut adjustment on
front castor double wheels.



Convogliatore per
sarmenti.
Front metal steel conveyor
for branches.

MAZZE STANDARD INCLUDED HAMMER



Mazza in acciaio forgiato e temperata
Mod. Super 1,5 Kg per tritrazione ramaglie
fino a 6 cm.
Forged steel and hardened hammer
Mod. Super 1,5 Kg for branches cut up to
6 cm in diameter.



MODELLO MODEL	 LT.	 Kg	 RPM	 LxPxH	 LxPxH
	(LT)	(KG)	(RPM)	(LxPxH)	(LxPxH)
CANGURO PROFESSIONAL SUPER 1600	1900	905	540	1980 x 2180 x 1590	2000 x 2250 x 1700
CANGURO PROFESSIONAL SUPER 1800	2100	1000	540	2180 x 2310 x 1590	2200 x 2250 x 1700