


ELEPHANT SUPER

**TRINCIAERBA/ TRINCIASARMENTI
CON RACCOLTA PER TRATTORI
DA 80 A 100 CV**

**CONTRACTOR FLAIL MOWER
FOR TRACTORS FROM 80 TO 100 HP**

VIDEO 



Caratteristiche

- Con raccolta e scarico in altezza a 200cm*
- Macchina molto robusta per lavori intensivi.
- Per utilizzo con trattori da 80 a 100CV
- Per superfici comunali, agricole (Vigneti e Frutteti) maneggi, ippodromi e orticoltura.
- Taglio erba fino a 200cm di altezza
- Cuscinetti UCC su albero coltelli ad alta resistenza da urti ed attriti.
- Moltiplicatore con ruota libera.
- Apertura raccogliitore idraulica con 2 prese.
- Rullo posteriore autopulente.

Features

- With collection and discharge at 200cm* height.
- Very sturdy machine for intensive work.
- For 80 to 100 HP tractors use.
- For municipal, agricultural fields (vineyards and orchards), stables, racetracks, and horticulture.
- Grass cutting up to 200 cm height.
- UCC bearings on flail shaft, highly resistant to impacts and friction.
- Gearbox with overrun clutch.
- Hydraulic collector opening with 2 quick couplings.
- Self-cleaning rear roller.




MODELLO MODEL		 (MIN - MAX)		
	(MM)	(HP)	(KW)	Nr.
ELEPHANT SUPER 2000	1920	80 - 95	60 - 71	28
ELEPHANT SUPER 2200	2130	90 - 100	67 - 74	30



Scarico idraulico oltre 2 mt
High lift discharge up to 2 mt



COMPONENTI TECNICHE DI SERIE TECHNICAL COMPONENTS STANDARD




MAZZE STANDARD INCLUDED HAMMER



Mazza in acciaio forgiato e temperata
Mod. Super 1,5 Kg per triturazione ramaglie
fino a 6 cm.
Forged steel and hardened hammer
Mod. Super 1,5 Kg for branches cut up to
6 cm in diameter.

ACCESSORI ACCESSORIES



Kit slitte laterali protezione
scocca.
Side skids kit protection
frame.



Kit luci posteriori.
Rear Transport Lights.

MODELLO MODEL	 LT.	 Kg			
	(LT)	(KG)	(RPM)	(LxPxH)	(LxPxH)
ELEPHANT SUPER 2000	2350	1170	540	2385 x 2270 x 1590	2400 x 2150 x 1600
ELEPHANT SUPER 2200	2600	1270	540	2585 x 2270 x 1590	2600 x 2150 x 1600